

BOGE Typ	Behälterinhalt Liter	Höchstdruck		Effektive Liefermenge*		Motorleistung		Abmessungen mit Kühlluftführungshaube (KFH) B x T x H (mm)	Abmessungen mit Schalldämmhaube (SDH) B x T x H (mm)	Gewicht (KFH) kg	Gewicht (SDH) kg
		bar	psig	l/min	cfm	kW	PS				
PO 3 L		6	90	268	9,5	2,2	3,0	759 x 811 x 694	–	114	–
		10*	145	246	8,7	2,2	3,0	759 x 811 x 694	–	114	–
PO 3 L		9	130	250	8,8	2,2	3,0	785 x 811 x 757	–	120	–
		15*	218	245	8,6	2,2	3,0	785 x 811 x 757	–	120	–
PO 4 L		6	90	398	14,1	3,0	4,0	759 x 811 x 694	–	120	–
		10*	145	362	12,8	3,0	4,0	759 x 811 x 694	–	120	–
PO 4 L		9	130	294	10,4	3,0	4,0	785 x 811 x 757	–	128	–
		15*	218	288	10,2	3,0	4,0	785 x 811 x 757	–	128	–
PO 6 L		6	90	524	18,5	4,0	5,5	759 x 811 x 694	–	127	–
		10*	145	512	18,1	4,0	5,5	759 x 811 x 694	–	127	–
PO 6 L		9	130	452	16,0	4,0	5,5	785 x 811 x 757	–	136	–
		15*	218	450	16,0	4,0	5,5	785 x 811 x 757	–	136	–
PO 8 L		6	90	704	24,9	5,5	8,0	759 x 811 x 694	–	137	–
		10*	145	668	23,6	5,5	8,0	759 x 811 x 694	–	137	–
PO 3 LR	90	10	145	246	8,7	2,2	3,0	759 x 1141 x 1110	–	182	–
	160	15	218	245	8,6	2,2	3,0	785 x 1380 x 1309	–	210	–
PO 4 LR	90	10	145	362	12,8	3,0	4,0	759 x 1141 x 1110	–	188	–
	160	15	218	288	10,2	3,0	4,0	785 x 1380 x 1223	–	205	–
PO 6 LR	160	10	145	512	18,1	4,0	5,5	759 x 1380 x 1223	–	212	–
	160	15	218	450	16,0	4,0	5,5	785 x 1380 x 1309	–	226	–
PO 8 LR	160	10	145	668	23,6	5,5	8,0	759 x 1380 x 1223	–	222	–
PO 3 LDR	160	10	145	246	8,7	2,2	3,0	759 x 1380 x 1223	–	222	–
	160	15	218	245	8,6	2,2	3,0	785 x 1380 x 1309	–	250	–
PO 4 LDR	160	10	145	362	12,8	3,0	4,0	759 x 1380 x 1223	–	228	–
	160	15	218	288	10,2	3,0	4,0	785 x 1380 x 1309	–	290	–
PO 6 LDR	160	10	145	512	18,1	4,0	5,5	759 x 1380 x 1223	–	252	–
	160	15	218	450	16,0	4,0	5,5	785 x 1380 x 1309	–	266	–
PO 8 LDR	160	10	145	668	23,6	5,5	8,0	759 x 1380 x 1223	–	262	–
PO 3 LTR	270	10	145	2 x 246	2 x 8,7	2 x 2,2	2 x 3,0	750 x 1950 x 1300	–	336	–
	350	15	218	2 x 245	2 x 8,6	2 x 2,2	2 x 3,0	770 x 1950 x 1430	–	358	–
PO 4 LTR	270	10	145	2 x 362	2 x 12,8	2 x 3,0	2 x 4,0	750 x 1950 x 1300	–	348	–
	350	15	218	2 x 288	2 x 10,2	2 x 3,0	2 x 4,0	770 x 1950 x 1430	–	400	–
PO 6 LTR	270	10	145	2 x 512	2 x 18,1	2 x 4,0	2 x 5,5	750 x 1950 x 1300	–	362	–
	350	15	218	2 x 450	2 x 16,0	2 x 4,0	2 x 5,5	770 x 1950 x 1430	–	432	–
PO 8 LTR	270	10	145	2 x 668	2 x 23,6	2 x 5,5	2 x 8,0	750 x 1950 x 1300	–	382	–

\* Liefermenge gemessen nach VDMA 4362 bei 80% Höchstdruck. Emissions-Schalldruckpegel nach P N8NTC2.3 ab 79 dB(A)